





**SGI TX**

- ① **POWER LED** - indicates the SGI TX is active when power supply is connected.
- ② **DRAG™** - load correction allows you to dial-in the proper load for your pickups.
- ③ **INPUT** - 1/4" jack for instrument connection.
- ④ **TRANSMIT** - XLR output transmits balanced mic-level signal to the SGI RX unit.
- ⑤ **POWER** - connection for included 15VDC power supply.

**SGI RX**

- ⑥ **RECEIVE** - XLR input receives balanced mic-level signal from SGI TX unit.
- ⑦ **OUTPUT** - 1/4" jack outputs guitar signal.
- ⑧ **GROUND LIFT** - reduces ground loop hum by disconnecting the ground path from pin-1 on the XLR jack.

**RADIAL LIMITED THREE YEAR TRANSFERABLE WARRANTY**

Radial Engineering - a division of JP Cabletek Electronics Ltd. warrants this product to be free from defects in material and workmanship to the original owner and will remedy any such defects free of charge according to the terms of this warranty. Radial Engineering will repair or replace at its option any defective component(s) of this product, excluding the finish, the footswitch (footswitch is warranted for 90 days) and wear and tear from normal use, for a period of three (3) years from the original date of purchase. In the event that a particular product is no longer available, Radial Engineering reserves the right to replace the product with a similar product of equal or greater value. To make a request or claim under this limited warranty, the product must be returned prepaid in the original shipping container (or equivalent) to Radial Engineering or to an authorized repair centre and you must assume the risk of loss or damage. A copy of the original invoice showing date of purchase and the dealer name must accompany any request for work to be performed under this limited warranty. This limited warranty shall not apply if the product has been damaged due to abuse, misuse, misapplication, accident or as a result of service or modification by any other than an authorized repair centre.

THERE ARE NO EXPRESSED WARRANTIES OTHER THAN THOSE ON THE FACE HEREOF AND DESCRIBED ABOVE. NO WARRANTIES, WHETHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, SHALL EXTEND BEYOND THE RESPECTIVE WARRANTY PERIOD DESCRIBED ABOVE OF THREE YEARS.

RADIAL ENGINEERING SHALL NOT BE RESPONSIBLE OR LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LOSS ARISING FROM THE USE OF THIS PRODUCT. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS, WHICH MAY VARY DEPENDING ON WHERE YOU LIVE.



SGI

STUDIO GUITAR INTERFACE

Users Guide

Part # R800 1600



Radial Engineering
1638 Kebet Way, Port Coquitlam BC V3C 5W9
Tel: 604-942-1001 Fax: 604-942-1010
email: info@radialeng.com

Congratulations on your purchase of the Radial SGI TX-RX studio guitar interface. The SGI has been designed and constructed to provide years of dependable performance whether it is used in the studio or on the road.

Your new SGI features a 100% discreet Class-A signal path to ensure optimum audio performance and is equipped with transformer isolation to eliminate buzz and hum caused by ground loops. To further assure sonic integrity, the SGI is equipped with Radial's unique Drag™ Control load correction circuit. Drag lets you apply the perfect load to counteract cable capacitance and buffering to ensure the natural tone and dynamics of your instrument are maintained.

Although the SGI is 'plug & play' easy to use, we recommend that you take a few minutes to read this short manual so that you get the most out of your Radial SGI. Should you have any questions that are not covered in this manual, we invite you to log onto www.radialeng.com and visit the FAQ section on our site. This is where we post the latest updates and applications from users like you.

Now get out there and play guitar with your amp on the other side of the lake!

INTRODUCTION

The Radial SGI studio guitar interface is delivered as a transmit TX and receive RX set that is connected together with a standard balanced twisted pair XLR microphone cable.

The SGI TX (or transmit module) is active buffered meaning that it requires power to drive the signal. A high output 15VDC power supply is employed to power the Class-A audio path and provides the horsepower to drive the signal. The SGI-RX (or receive module) is passive. This means that it does not require any power.

The SGI is designed to transmit high impedance guitar signals to 100 meters (330 feet) and beyond. With these distances in mind, it is likely that each end will be connected to equipment that will in turn, be powered by different electrical circuits. To alleviate noise problems caused by potential ground loops, the SGI is equipped with isolation transformers at each end that have been matched and counter-wired to offset any artifact.

The bright yellow finish increases visibility to make finding each end as easy as possible, while construction is 14 gauge steel and features welded I-beam construction to eliminate potential stress on the PC board.

USING THE SGI

As always, before making any audio connection, ensure audio system power is off and volume controls are turned down. This practice eliminates popping caused by power-up transients that could damage loudspeakers or other components.

Begin by connecting your instrument to the SGI-TX, an XLR cable between the TX and RX module, and the RX module to your guitar amp or pedals. You can now connect the 15VDC power supply to the SGI-TX module. There is no power switch. As soon as you connect the supply the LED should illuminate telling you power is on.

Although the SGI has been optimized for guitar, you can use it with any high-impedance instrument. Just be careful with high output devices such as keyboards, as these could overload the input if driven too hard. If you intend to use your SGI with high output instruments, simply listen to the signal to make sure it is clean and distortion free. If you hear distortion, it is likely the keyboard signal is too hot. Turn it down and you should be set to go.




The Radial SGI-RX is passive. The only control on the RX is a ground lift. This lifts pin-1 ground on the XLR receive and is used to further eliminate ground loops should hum or buss be encountered.

DRAG™ CONTROL

The Radial SGI-TX is equipped with a recessed knob called Drag control. This unique load correction circuit allows you to apply a resistive-capacitive load on your pickup to counteract any effect of the buffering circuit or cable. It is designed specifically for passive guitar pickups that are most sensitive to the input impedance of an amplifier. Drag will have almost no effect on active devices such as keyboards.

For best results, we suggest that you start with a clean tone and set the Drag control to 50% or 12 o'clock and then adjust to suit. More drag will result in a darker tone, while less drag will reduce the load on the pickup and add sparkle. Simply find the setting that you like using a guitar pick as a screwdriver and you are set. Drag control is subtle yet very musical.

You are now set to go!



FAQ

Can I use the SGI as a re-amping device?

No. The Radial SGI employs a proprietary balanced signal between the TX transmit module and the RX receive module, making it unsuitable for typical line-level signals.

Can I use other instruments such as a keyboard or even voice through the SGI?

Yes. Just make sure you do not overload the input as this will cause distortion. Keep in mind that the SGI is designed for guitar levels. Keyboards and line-level outputs are significantly more powerful and should be attenuated.

Why is the SGI bright yellow?

So you will be able to find the other end! Many studios are outfitted with a labyrinth of connector panels and the SGI can easily be left in one place or another. Bumble bee yellow should make tracking the SGI easy!

Does the Drag control have any effect on active pickups?

You will hear very little effect, if any, when using active instruments, as their buffered outputs will generally not be affected by an added load. The SGI's Drag control is really designed to affect passive electric guitars.

Can I connect effect pedals between the SGI and my guitar amp?

Yes of course! The SGI will work just like your guitar, except you will be able to play your amp several hundred feet away.

Can I use the SGI on a large stage to drive my amp?

Yes. Although we have other products in our Tonebone range such as the Switchbone and Loopbone that can do this very well for distances up to 50 feet.

Could the SGI cause noise or cross talk in a live touring snake system?

The SGI is completely analogue and is low level. You should not encounter any of these problems using the SGI.