

1583A Multi-Conductor - Category 5e Nonbonded-Pair Cable



For more Information
please call

1-800-Belden1



General Description:

CAT5e (200MHz), 4-Pair, U/UTP-Unshielded, Riser-CMR, Premise Horizontal Cable, 24 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Ripcord, PVC Jacket.

Usage (Overall)

Suitable Applications: Horizontal, 1000BaseT, Gigabit Ethernet, POE, POE+, 100BaseTX, Fast Ethernet, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Video, RS-422

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 24 | Solid | BC - Bare Copper |

Total Number of Conductors: 8

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Diameter:

| Nom. Dia. (in.) |
|-----------------|
| 0.190 |

Outer Jacket Ripcord: Yes

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

| | |
|--|-----------------|
| Storage Temperature Range: | -20°C To +75°C |
| Installation Temperature Range: | 0°C To +60°C |
| Operating Temperature Range: | -20°C To +60°C |
| Bulk Cable Weight: | 18 lbs/1000 ft. |
| Max. Recommended Pulling Tension: | 35 lbs. |
| Min. Bend Radius/Minor Axis: | 0.800 in. |
| Min. Bend/Installation: | 1.900 in. |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|--------------------------------|-----|
| NEC/(UL) Specification: | CMR |
| NEC Articles: | 800 |

1583A Multi-Conductor - Category 5e Nonbonded-Pair Cable

| | |
|---------------------------------------|-------------------------------------|
| CEC/C(UL) Specification: | CMR |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| Other Standards: | ISO/IEC 11801 ed 2.1 (2008) Class D |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | Category 5e - TIA 568.C.2 |
| Other Specification: | NEMA WC-63.1 Category 5e |

Applicable Patents:

| |
|------------------|
| Country |
| www.belden.com/p |

Flame Test

| | |
|-------------------|-----------------------|
| UL Flame Test: | UL1666 Vertical Riser |
| C(UL) Flame Test: | FT4 |
| CSA Flame Test: | FT4 |
| IEEE Flame Test: | 1202 |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | No |
| Suitability - Aerial: | No |
| Suitability - Burial: | No |
| Sunlight Resistance: | No |
| Oil Resistance: | No |
| Non-halogenated: | No |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

| |
|----------------------------|
| Capacitance (pF/ft) |
| 15 |

| | |
|---|-----|
| Maximum Capacitance Unbalance (pF/100 m): | 330 |
|---|-----|

Nominal Velocity of Propagation:

| |
|---------------|
| VP (%) |
| 70 |

Maximum Delay:

| |
|-------------------------|
| Delay (ns/100 m) |
| 538 @ 100MHz |

Max. Delay Skew:

| |
|------------------------------|
| Delay Skew (ns/100 m) |
| 45 |

Maximum Conductor DC Resistance:

| |
|-------------------------------|
| DCR @ 20°C (Ohm/100 m) |
| 9.38 |

Max. Operating Voltage - UL:

| |
|----------------|
| Voltage |
| 300 V RMS |

Maximum DCR Unbalanced:

| |
|---------------------------------|
| DCR Unbalance @ 20°C (%) |
|---------------------------------|

1583A Multi-Conductor - Category 5e Nonbonded-Pair Cable

3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|
| 1 | 2.000 | 65.3 | 62.3 | 63.0 | 60.3 | 20.000 |
| 4 | 4.100 | 56.3 | 53.3 | 51.0 | 49.2 | 23.000 |
| 8 | 5.800 | 51.8 | 48.8 | 46.0 | 43.0 | 24.500 |
| 10 | 6.500 | 50.3 | 47.3 | 43.0 | 40.8 | 25.000 |
| 16 | 8.200 | 47.3 | 44.3 | 39.0 | 36.0 | 25.000 |
| 20 | 9.300 | 45.8 | 42.8 | 36.5 | 33.5 | 25.000 |
| 25 | 10.400 | 44.3 | 41.3 | 33.9 | 30.9 | 24.300 |
| 31.25 | 11.700 | 42.9 | 39.9 | 31.0 | 28.2 | 23.600 |
| 62.5 | 17.000 | 38.4 | 35.4 | 22.0 | 19.0 | 21.500 |
| 100 | 22.000 | 35.3 | 32.3 | 14.0 | 10.3 | 20.100 |
| 155 | 28.100 | 32.5 | 29.5 | 4.4 | 1.4 | 15.800 |
| 200 | 32.400 | 30.8 | 27.8 | 4.0 | 1.0 | 15.000 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|--------------------|
| 1 | 100 ± 15 | 63.8 | 60.8 |
| 4 | 100 ± 15 | 51.7 | 48.7 |
| 8 | 100 ± 15 | 45.7 | 42.7 |
| 10 | 100 ± 15 | 43.8 | 40.8 |
| 16 | 100 ± 15 | 39.7 | 36.7 |
| 20 | 100 ± 15 | 37.7 | 34.7 |
| 25 | 100 ± 15 | 35.8 | 32.8 |
| 31.25 | 100 ± 15 | 33.9 | 30.9 |
| 62.5 | 100 ± 15 | 27.8 | 24.9 |
| 100 | 100 ± 15 | 23.8 | 20.8 |
| 155 | 100 ± 25 | 19.9 | 16.9 |
| 200 | 100 ± 25 | 17.7 | 14.7 |

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft. intervals. Third party verified to ANSI/TIA-568-C.2, Category 5e. Values above 100 MHz are for engineering purposes only.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|----------|-------------|-------------|-------|--------------------------|
| 1583A 002U1000 | 1,000 FT | 24.000 LB | RED | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0021000 | 1,000 FT | 5.000 LB | RED | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 003U1000 | 1,000 FT | 24.000 LB | ORANGE | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0031000 | 1,000 FT | 20.000 LB | ORANGE | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 004U1000 | 1,000 FT | 24.000 LB | YELLOW | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0041000 | 1,000 FT | 20.000 LB | YELLOW | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 005U1000 | 1,000 FT | 24.000 LB | GREEN, DARK | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0051000 | 1,000 FT | 20.000 LB | GREEN, DARK | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 006U1000 | 1,000 FT | 20.000 LB | BLUE, LIGHT | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0061000 | 1,000 FT | 20.000 LB | BLUE, LIGHT | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 0061640 | 1,640 FT | 34.440 LB | BLUE, LIGHT | | CAT5E 4PR U/UTP CMR REEL |
| 1583A 0063000 | 3,000 FT | 60.000 LB | BLUE, LIGHT | | CAT5E 4PR U/UTP CMR REEL |
| 1583A 008U1000 | 1,000 FT | 20.000 LB | GRAY | C | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0081000 | 1,000 FT | 20.000 LB | GRAY | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 0081640 | 1,640 FT | 34.440 LB | GRAY | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 0083000 | 3,000 FT | 60.000 LB | GRAY | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 009U1000 | 1,000 FT | 24.000 LB | WHITE | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0091000 | 1,000 FT | 20.000 LB | WHITE | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 0093000 | 3,000 FT | 60.000 LB | WHITE | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 010U1000 | 1,000 FT | 24.000 LB | BLACK | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0101000 | 1,000 FT | 20.000 LB | BLACK | C | CAT5E 4PR U/UTP CMR REEL |
| 1583A 012U1000 | 1,000 FT | 24.000 LB | PINK | | CAT5E 4PR U/UTP CMR BOX |
| 1583A 0121000 | 1,000 FT | 20.000 LB | PINK | C | CAT5E 4PR U/UTP CMR REEL |

Notes:
C = CRATE REEL PUT-UP.

1583A Multi-Conductor - Category 5e Nonbonded-Pair Cable

Revision Number: 6 Revision Date: 06-09-2016

© 2017 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).