

Bridge X_TS

Trouble Shooter



MIRRORING OUTPUT [HDMI]



Variety IN/OUT
Signal Converting



A/V Installation, Repair
and Maintenance



Audio MUX/DEMUX



Touch Display

Trouble Shooter Premium Converter



Bridge X_TS



Descriptions

Bridge X TS is a device that supports a variety of inputs and outputs. This device can be used in a installation construction, maintenance service of video or audio signal. You can see the signal status Through the LCD panel. even in case that one input signal is applied, all the output provide its converted signals Also this device has the ability to measure the built-in SDI Jitter and Cable length

Feature

- Up/Down/Cross/Scan converter
- Multiple standard Video / Audio signal
- (CVBS, AES/EBU, SDI, VGA, COMPONENT, Analog audio, HDMI)
- Analog audio MUX / DEMUX
- User selectable output format
- Test Pattern Generator (Stop screen and Moving Box screen)
- Menu OSD function
- Audio level check (Most 8 channels are monitored)
- Touch Screen LCD Built in For Input signal monitoring (5 Inch 800x480)
- External Battery (Option)


Physical

Dimension (W x H x D)	182.4 x 92.6 x 29 (mm)
Weight	530g
Power Level	+12 VDC
Power Consumption	19 Watts
Operating Temperature	-20°C ~ 70°C
Humidity	0 to 95% RH, non-condensing

Image View



Drawing Dimension [mm]



Digital Video Specs.

- Supports HDMI v1.3
- Supports VGA, Comp, CVBS format
- Supports multi-rate SDI formats
- SMPTE 125M: NTSC (480i 59.94), PAL (576i 50)
- SMPTE 296M: 720p (60/59.94/50)
- SMPTE-274M: 1080i (60/59.94/50)
- SMPTE-292M: 1080p (30/29.97/25/24/23.98)
- SMPTE-424M: 1080p (60/59.94/50) 3G

LCD Display Specs.

- Size: 5.0 Inch
- Resolution : 800 x 480
- Pixel area : 0.135mm(W) x 0.135mm(H)
- Display area : 108mm(W) x 64.8(H)

Application

